

MKU LNA 231 AH, Super Low Noise Preamplifier
2304 ... 2322 MHz

Super Low Noise Preamplifier for DX and EME



Description

For many years, our super low noise microwave preamplifier has been used very successful. Many results of Ham Radio Contests proof that! Due to a extremely low noise figure the preamplifier is ideal for tropo DX, EME (earth moon earth operation) and for receiving satellites.

Features

- Extremely low noise figure
- Unconditionally stable - no parasitic oscillations in case of poor antenna match
- Reverse polarity protection
- Solder pin for direct power supply
- Male connector at the input for direct connection to antenna or coaxial relay
- Small mechanical dimensions

Applications

- Amateur Radio
- EME, Tropo DX, satellite reception
- Analog and digital operation modes (SSB, CW, WSJT)

Important notes

- Amplifier does not contain a coaxial relay!
- Maximum input power 1 mW

Technical specifications:

Frequency range	2304..2322 MHz
Noise figure @ 18 °C	typ. 0.4 dB
Gain	typ. 16 dB
Maximum input power	1 mW
Supply voltage	+9 ... 15 V DC
Current consumption	typ. 15 mA
Input connector / impedance	N-male, 50 ohms
Output connector / impedance	N-female, 50 ohms
Case	milled aluminium
Dimensions (mm)	50 x 30 x 22
Weight	110 g (typ.)