

# MKU PA 70CM-60W HY, UHF MOSFET-Power Amplifier

430 ... 440 MHz • 60 W

UHF MOSFET Power Amplifier for the Amateur Radio Band 70 cm

List price: 499,00 EUR



#### **Features**

- Good linearity
- Built-in low pass filter for good harmonic rejection
- Reverse polarity protection
- Monitor output for forward power detection

### **Applications**

- Analog and digital transmission systems
- Power amplifier for radio amateur applications (SSB, CW)

### Important notes

Please notice the following:

- Recommended output power for radio amateur applications: Modulation type: CW/FM up to 60 W, SSB up to 20 W
- The technical specifications refer to room temperature.
- The power amplifier doesn't contain any coaxial relays.
- The recommended combination of heat sink and fan(s) is only specified for an ambient temperature of 25 °C.
- Further information about dimensioning of heat sinks is available on our FAQ site.

## Industrial use

Our power amplifiers of the MKU-series are exclusively intended for amateur radio applications and will only be sold to radio amateurs with a licence. These products are specified for amateur radio requirements and are not designed for industrial applications. Please notice our list of industrial products or ask for a special version.

Technical specifications:	
Frequency range	430440 MHz
Input power	typ. 50 mW
Maximum input power	100 mW
Saturation power	typ. 60 W
Gain (small signal)	min. 34 dB
Harmonic rejection	typ. 60 dB
Supply voltage	+12 14 V DC
Quiescent current	typ. 4 A
Current consumption	max. 10 A
Operating case temp. range	-20 +55 °C
VSWR of load	max. 1.8 : 1
Input connector / impedance	SMA-female / 50 ohms
Output connector / impedance	N-female / 50 Ohms
Case	milled aluminium
Dimensions (mm)	130 x 60 x 20
Weight	270 g (typ.)