

KU PA 330360-40 LIN, LDMOS Power Amplifier

3300 ... 3600 MHz • 4 ... 5 W COFDM

Linear S-Band Power Amplifier

- Digital predistortion (DPD)
- Remote control via serial interface



5 W COFDM

Description

Find a detailed description under downloads.

Features

- LDMOS technology
- High linearity (build-in linearizer)
- Good harmonic rejection
- Isolator for protection against high VSWR
- Adjustable ALC (automatic level control)
- True-RMS Detector output for forward and reverse power detection (DC voltage)
- Logic ON / OFF control (ON at 3 ... 14 V)
- serial interface

Applications

- Digital broadcast systems (DVB-T, DVB-S)
- COFDM systems using modulation types QPSK, QAM
- Multichannel Multipoint Distribution Service (MMDS)

Important notes

Please notice the following:

- The technical specifications refer to room temperature.
- The power amplifier doesn't contain any coaxial relays.
- The recommended combination of heat sink and fan(s) is only specified for an ambient temperature of 25 °C.
- Further information about dimensioning of heat sinks is available on our FAQ site.

Technical specifications:

Frequency range	3300..3600 MHz
Input power	+5 ... 10 dBm
Maximum input power	+10 dBm
Output power COFDM (1)	typ. 5 W, min. 4 W
Automatic level control (ALC)	yes (adjustable ALC)
Gain flatness (small signal)	typ. +/- 1 dB
Harmonic rejection	typ. 50 dB @ 37 dBm
VSWR protection	Isolator
ON voltage	+3 ... 14 V DC
Supply voltage	+28 ... 32 V DC
Quiescent current	typ. 0.8 A
Current consumption	typ. 2.0 A @ 5 W
Forward detection	yes (True RMS detector)
Reflected power detection	yes (True RMS detector)

Operating case temp. range	-20 ... +55 °C
Input connector / impedance	SMA-female / 50 ohms
Output connector / impedance	SMA-female / 50 ohms
Case	milled aluminium
Dimensions (mm)	184 x 100 x 20
Weight	550 g (typ.)